



ADVANCED CABLE TIES PART NUMBER	BUNDLE DIAMETER		A IN (mm) +/- .625 (15.875mm)	B IN (mm) +/- .005 (.127mm)	C IN (mm) +/- .005 (.127mm)	D IN (mm) +/- .020 (.508mm)	E IN (mm) +/- .020 (.508mm)	F IN (mm) +/- .005 (.127mm)	MIN LOOP TENSILE LBS (N)	ANSI/UL 94 MH FLAMABILITY RATING	PLENUM RATING
	MIN IN (mm)	MAX IN (mm)									
AP(R, L)-24-175-9	1.500 (38.1mm)	7.18 (182.3mm)	25.500 (647.700mm)	.090 (2.286mm)	.340 (8.636mm)	.555 (14.097mm)	.335 (8.509mm)	.550 (13.970mm)	175 (778)	V-2	AH-2
AP(R, L)-24-175-0	1.500 (38.1mm)	7.18 (182.3mm)	25.500 (647.700mm)	.090 (2.286mm)	.340 (8.636mm)	.555 (14.097mm)	.335 (8.509mm)	.550 (13.970mm)	175 (778)	V-2	AH-2
AP(R, L)-36-175-9	1.500 (38.1mm)	11.000 (279.400mm)	37.250 (946.150mm)	.090 (2.286mm)	.340 (8.636mm)	.555 (14.097mm)	.335 (8.509mm)	.550 (13.970mm)	175 (778)	V-2	AH-2
AP(R, L)-36-175-0	1.500 (38.1mm)	11.000 (279.400mm)	37.250 (946.150mm)	.090 (2.286mm)	.340 (8.636mm)	.555 (14.097mm)	.335 (8.509mm)	.550 (13.970mm)	175 (778)	V-2	AH-2
AP(R, L)-48-175-9	1.500 (38.1mm)	14.500 (368.300mm)	48.562 (1233.474mm)	.090 (2.286mm)	.340 (8.636mm)	.555 (14.097mm)	.335 (8.509mm)	.550 (13.970mm)	175 (778)	V-2	AH-2
AP(R, L)-48-175-0	1.500 (38.1mm)	14.500 (368.300mm)	48.562 (1233.474mm)	.090 (2.286mm)	.340 (8.636mm)	.555 (14.097mm)	.335 (8.509mm)	.550 (13.970mm)	175 (778)	V-2	AH-2



175 LB. HEAVY DUTY SERIES CABLE TIES

F	5/7/20	DW	RB	ADDITION OF AP(R, L)-48-175-8							
G	11/9/18	KT	DW	REVISE LENGTH TOLERANCE							
F	8/27/18	EG	DW	DISCONTINUED/ REMOVED 33" CABLE TIES							
E	3/9/18	PB	EG	REMOVED 250 LB. CABLE TIES TO NEW SPEC DRAWING							
D	8/25/17	JA	KT	REVISE 24" LENGTH & TOLERANCE							
C	5/18/17	JA	KT	24-175 LENGTH CORRECTION							
B	5/1/17	JA	KT	NEW LOGO ADDED							
A	12/22/14	JA	KT	INITIAL RELEASE							
REV	DATE	BY	CHK	APPROVE	DESCRIPTION	SHEET 1 OF 1	REV.: F	DATE	CHECK	SCALE	DRAWING NO.: 175-F
						JA	8/25/2017	KT		NONE	

COLOR DESIGNATIONS:  
0 = UV BLACK 9 = NATURAL 8=GRAY

MATERIAL:  
**NYLON 6/6 POLYAMIDE**

THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.

SPC-4.10.49.3