



PART NUMBER

308605 #40 Cylinder (clear)

TECHNICAL DATA

Color	White
Consistency	Aerosol spray
Spray Pattern	Variable web
Odor	Mint when wet
Base	Polymer
Vapor Pressure	350 mm
Solvent	Methyl Acetate, Hexane, Tertiary Butyl Acetate
Approx. Coverage	125 sq ft/lb of adhesive
Initial Bonding Time	Immediate
Dry Time	4 minutes
Adhesion	Excellent
Service Temperature	-40°F to 200°F
Surface Burning	Flame spread 0. Smoke developed 10. When tested in accordance with ASTM E84.
Flammability	Flammable when wet (flame projection test). Nonflammable when dry.
Water Resistance	Excellent
Mildew Resistance	Good
VOC	<61 g/l
Packaging	#40 Aerosol cylinder

SPECIFICATION/STANDARDS COMPLIANCE

Property	Method	Results
Duct Thermal Insulation	ASTM C916	Pass
VOC Limitation	SCAQMD Rule 1168	Pass
	Ozone Transport Commission (OTC)	Pass
	City of Los Angeles Approved RR #8069	Pass

Low-VOC Travel-Tack is a self-contained, instant-tacking portable spray system engineered to deliver a Low-VOC compliant adhesive. The web spray pattern eliminates adhesive vaporization and overspray. Travel-Tack's portability, limited equipment clean-up, and low equipment cost make this adhesive ideal for shop or field use.

APPLICATION

Temperature	60°F to 90°F (15.5°C to 32.2°C) (Keep at 70°F for optimum performance. If cylinder temperature falls below 70°F, move it to a warm area until optimum performance is achieved.)
Method	Apply according to SMACNA specifications and local codes.
Preparation	Surface must be dry and free of dirt, oil, moisture and grease.
Rate	16-oz per minute
Clean Up	UN-TACK Cleaner/Adhesive Remover, petroleum solvents or mineral spirits

STORAGE

Temperature	60°F to 95°F (15°C to 35°C)
Shelf Life	One year (unopened)

PRECAUTIONS

- Do not expose to heat or store above 100°F.
- Do not puncture or incinerate.
- Canisters are not re-fillable. When empty, dispose by following local code requirements.
- Review Material Safety Data Sheet for safety information prior to use.

For Industrial Professional Use Only.