

D U C T M A T E

Quick-Stick™



Non-Flammable Spray Adhesive



Premium Quality

- Pressure sensitive
- Methylene chloride based
- High solids content
- Easy application
- Extremely quick tack
- Strong permanent bond
- Meets DOT 39 NRC
- Non-Flammable in wet and dry state
- Exceptional coverage
- Convenient 12, 40, and 375 lb. cylinders
- This product contributes to satisfying LEED EQ. Credit 4.1



DUCTMATE®
Industries, Inc.

GASKETS, SEALANTS, ADHESIVES

Quick-Stick™

Non-Flammable Spray Adhesive

DESCRIPTION

Quick-Stick is a premium quality, completely non-flammable, pressure sensitive adhesive specifically formulated for a quick permanent tack.

BASIC USE

To provide a versatile convenient means for bonding insulation, or other materials to smooth nonporous surfaces.

SPECIAL CHARACTERISTICS

Pressure sensitive
Methylene chloride based
High solids content
Easy application
Extremely quick tack
Strong permanent bond
Meets DOT 39 NRC
Non-Flammable in wet and dry state
Exceptional coverage
Convenient 12, 40, and 375 lb. cylinders
This product contributes to satisfying LEED EQ. Credit 4.1

PACKAGING INFORMATION

Part No.	Description	Quantity/Weight
QuickStick12	12 lbs	1 EA@12 lbs.
QuickStick40	40 lbs.	1 EA@40 lbs.
QuickStick375	375 lbs.	1 EA@375 lbs.
QSSG	Quick-Stick Spray Gun	1 EA @ 1 lb.
QSH6	Quick-Stick 6' Hose	1 EA @ 1 lb.
QSH12	Quick-Stick 12' Hose	1 EA @ 1 lb.
QSH18	Quick-Stick 18' Hose	1 EA @ 2 lbs.

TECHNICAL INFORMATION

BASE: Solvent
SOLVENT: Methylene Chloride
COLOR: Green
SOLIDS: 25%
SERVICE TEMPERATURE: -30°F - 160°F
APPLICATION TEMPERATURE: 60°F - 90°F

TECHNICAL INFORMATION

STORAGE TEMPERATURE: Below 120°F
FLAMMABILITY: None
FLASHPOINT: None
FREEZE THAW: Does not apply
COVERAGE: 375 lb. - 37,500 sq. ft. - 43,125 sq. ft.
40 lb. - 4000 sq. ft. - 4600 sq. ft.
12 lb. - 1200 sq. ft. - 1385 sq. ft.
(Depending on temperature, humidity, and thickness)
BONDING TIME: 1-10 minutes
(Depending on application rate)
SHELF LIFE: 1 Year
PACKAGING: Available in 12, 40, 375 lb. containers

APPLICATION

Apply using industry approved spray equipment to smooth nonporous surfaces. Surfaces should be free from all dirt, oil, and grease.

DIRECTIONS:

Keep cylinder off of concrete floor during freezing temperatures. For best results use at temperatures between 60°F - 90°F.

1. Make sure all surfaces to be sprayed are clean and free from debris, dust, dirt, grease, etc.
2. Try gun on a test surface to make sure adhesive is flowing.
3. Hold spray gun 8-10 inches from surface to be sprayed.
4. Avoid buildup of adhesive or bubbles. Edges of spray pattern should overlap giving consistent coverage over surface.

FOR PERMANENT BOND: Spray both surfaces, bond activates from moment of contact with adhesive, bond will be permanent after 2 minutes.

LIMITED PRODUCT WARRANTY

Manufacturer is not liable for consequential, incidental or special damages. There are no statutory or implied warranties including the warranties for fitness for a particular purpose and merchantability. There are no warranties other than as set forth below and factory neither assumes nor authorizes any person to assume any liability or other obligation in connection with Quick-Stick.

Quick-Stick is warranted to be free from any and all defects in material and workmanship at the time of shipment from our factory, manufacturer will at its sole option, replace or issue credit for the original purchase price only.

Manufacturer does not guarantee the results from the use of Quick-Stick because of the extreme differences in surface textures of coated materials and the possibility of structural movement or externally caused damages.



CHARLEROI, PA
210 Fifth Street
Charleroi, PA 15022
800-245-3188
724-258-0500
FAX: 724-258-5494

LODI, CA
810 S. Cluff Avenue
Lodi, CA 95240-3141
800-344-3270
209-333-4680
FAX: 209-333-4678

www.ductmate.com

Distributed By:

Ductmate is a proud member
of the following organizations:



307/5-07